

## LEED® Product Statement

Effective Date: 10/01/15

The LEED® (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings.

## Panel 15<sup>®</sup> manufactured by Citadel Architectural Products,

carries the following attributes under the context of this standard:

- The product is manufactured in Greenfield, IN.
- The composite panel is warranted for a period of 5 years.
- Polyester and Acrylic Urethane painted finishes are warranted for a period of 5 years.
- The bonding agent used contains no VOCs, no formaldehyde, is non-hazardous, chemically inert, and is 100% solid (no solvents).

In addition, the following information can be used to determine the level of contribution towards satisfying MR Credit 4.1 and MR Credit 4.2(1)

## Panel 15

|  |                               | RECYCLED CONTENT BY WEIGHT |                    |
|--|-------------------------------|----------------------------|--------------------|
| COMPOSITION <sup>(2)</sup>   | WEIGHT (LBS/FT <sup>2</sup> ) | POST-CONSUMER              | POST-INDUSTRIAL(4) |
| <ul><li>Prefinished Textured Aluminum</li><li>Douglas Fir Plywood</li><li>Fiberglass Reinforced</li><li>Foil Scrim</li></ul> | 1.01                          | 0.4%                       | 5.0%               |

(1) MR Credit 4.1 and MR Credit 4.2 are based upon recycled content (as defined by the Green Building Rating System For New Construction & Renovations, ver 2.2) and are used to determine the overall dollar value of recycled material within the building.

(4) Post-Industrial is also referred to as Pre-Consumer.

**Citadel Architectural Products** 

6198 W Airport Blvd Greenfield, IN 46140 (800) 446-8828 www.citadelap.com • info@citadelap.com





Citadel Architectural Products has implemented a Quality Management System in accordance with ISO 9001:2015.

<sup>(2)</sup> General composition listed. For a detailed listing of components, refer to the Product Data Sheet.

<sup>(3)</sup> Due to variables within the manufacturing process, recycled content is based upon an average.